


TYPE HHK



TYPE HHK...2RS

Code Type HHK	Code Type HHK...2RS	ØP	ØD	S	C	α	FC (kN)	kg
HGE0001521	HGE0001526	20	35	16	12	9	31,5 - 68	0,06
HGE0001522	HGE0001527	25	42	20	16	7	51 - 130	0,11
HGE0001523	HGE0001528	30	47	22	18	6	65,5 - 170	0,14
	HGE0001529	35	55	25	20	6	220	0,22
	HGE0001530	40	62	28	22	7	280	0,30
	HGE0001531	45	68	32	25	7	360	0,40
	HGE0001532	50	75	35	28	6	440	0,54
	HGE0001533	60	90	44	36	6	690	1,00
	HGE0001534	70	105	49	40	6	880	1,50
	HGE0001535	80	120	55	45	6	1135	2,20
	HGE0001536	90	130	60	50	5	1375	2,70
	HGE0001537	100	150	70	55	7	1725	4,30
	HGE0001538	110	160	70	55	6	1860	4,70
	HGE0001539	120	180	85	70	6	2700	8,00

FC = MAX DYNAMIC LOAD

COUPLING : CROMO DURO/PTFE - HARTCHROM/PTFE - CHROM/PTFE

MATERIAL :  
STEEL ISO 12240-1 SERIE E