



Code	ØP	Z	S	ØD	S1	L	ØD2	ØG	FC (kN)	kg
*HBJE010C00	10	24	9	29	7	38,5	15	3	8,15	0,04
*HBJE012C00	12	27	10	34	8	44	17,5	3	10,8	0,06
**HBJE015C00	15	31	12	40	10	51	21	4	17	0,12
HBJE016C00 (A)	16	35	14	46	11	58	24	4	19	0,17
**HBJE017C00	17	35	14	46	11	58	24	4	21,2	0,18
HBJE020C00	20	38	16	53	13	64,5	27,5	4	30	0,26
HBJE025C00	25	45	20	64	17	77	33,5	4	48	0,45
HBJE030C00	30	51	22	73	19	87,5	40	4	62	0,67
HBJE035C00	35	61	25	82	21	102	47	4	80	1,02
HBJE040C00	40	69	28	92	23	115	52	4	100	1,40
HBJE045C00	45	77	32	102	27	128	58	6	127	1,93
HBJE050C00	50	88	35	112	30	144	62	6	156	2,69
HBJE060C00	60	100	44	135	38	167,5	70	6	245	4,60
HBJE070C00	70	115	49	160	42	195	80	6	315	7,00
HBJE080C00	80	141	55	180	47	231	95	6	400	11,00

FC = CARICO DINAMICO AMMESSO - MAX DYNAMIC LOAD - MAX DYNAMISCHE LAST

* NON RILUBRIFICABILE - WITHOUT GREASE NIPPLE - NICHT NACHSCHMIERBAR

** RILUBRIFICABILE MEDIANTE FORO - LUBRICATING HOLE IN THE HEAD - DURCH BOHRUNG NACHSCHMIERBAR

(A) = FUORI NORMATIVA - WITHOUT STANDARD - AUßER NORM

MATERIALE - MATERIAL: ACCIAIO - STEEL - STAHL ISO 12240-4 SERIE E - TIPO S