



Code	ØP	Z	S	ØD	S1	L	FC (kN)	kg
HBJE015N00	15	31	12	45	16	53,5	17	0,22
**HBJE016N00	16	35	14	48	17,5	59	21,2	0,29
HBJE017N00	17	35	14	48	17,5	59	21,2	0,29
HBJE020N00	20	38	16	50	19	63	30	0,36
HBJE025N00	25	45	20	55	23	72,5	48	0,53
HBJE030N00	30	51	22	65	28	83,5	62	0,85
HBJE035N00	35	61	25	83	30	102,5	80	1,50
HBJE040N00	40	69	28	100	35	119	100	2,42
HBJE045N00	45	77	32	110	40	132	127	3,39
HBJE050N00	50	88	35	123	40	149,5	156	4,24
HBJE060N00	60	100	44	140	50	170	245	7,10
HBJE070N00	70	115	49	164	55	197	315	10,70
HBJE080N00	80	141	55	180	60	231	400	15,10
HBJE090N00 (1)	90	150	60	226	65	263	490	23,40
HBJE100N00 (1)	100	170	70	250	70	295	610	33,10
HBJE110N00 (1)	110	185	70	295	80	332,5	655	48,50
HBJE120N00 (1)	120	210	85	360	90	390	950	79,50

FC = MAX DYNAMIC LOAD

** LUBRICATING HOLE IN THE HEAD -

(1) = PROFILE PLATE

MATERIAL STEEL - ISO 12240-1 SERIE E