



Code	ØP	Z	S	ØD	S1	L	F	LF	FC (kN)	kg
*HBJEPR612C	12	38	12	32	11	54	M12x1,25	17	10,8	0,11
HBJEPR616C	16	44	16	40	13	64	M14x1,5	19	17,6	0,20
HBJEPR620C	20	52	20	47	17	77	M16x1,5	23	30	0,35
HBJEPR625C	25	65	25	58	22	96	M20x1,5	29	48	0,62
HBJEPR632C	32	80	32	71	28	118	M27x2	37	67	1,15
HBJEPR640C	40	97	40	90	33	146	M33x2	46	100	2,18
HBJEPR650C	50	120	50	109	41	179	M42x2	57	156	3,96
HBJEPR663C	63	140	63	136	53	213	M48x2	64	255	6,80
HBJEPR670C (**)(A)	70	160	70	155	57	245	M56x2	76	315	9,60
HBJEPR680C (**)	80	180	80	170	67	270	M64x3	86	400	13,00
HBJEPR690C (**)(A)	90	195	90	185	72	296	M72x3	91	490	19,10
HBJEPR695C (**)	100	210	100	211	85	322	M80x3	96	610	25,00
HBJEPR696C (**)(A)	110	235	110	235	88	364	M90x3	106	655	32,00
HBJEPR697C (**)	125	260	125	265	103	406,5	M100x3	113	950	46,00

FC = MAX DYNAMIC LOAD

* WITHOUT GREASE NIPPLE

(A) =WITHOUT STANDARD

MATERIAL :

STEEL - ISO 12240-4 SERIE E (**) = NODULAR CAST IRON