



Code	ØAL	ØT	S	S1	kg	Box	Pcs
HCC00025035	25	35	7	2	0,04	BOXHCC00025035	250
HCC00030040	30	40	8	2	0,06	BOXHCC00030040	250
HCC00032042	32	42	8	2	0,10	BOXHCC00032042	250
HCC00035045	35	45	10	2	0,11	BOXHCC00035045	200
HCC00040050	40	50	10	2	0,13	BOXHCC00040050	150
HCC00045055	45	55	10	2	0,16	BOXHCC00045055	100
HCC00050060	50	60	10	2	0,19	BOXHCC00050060	100
HCC00055065	55	65	12	2	0,28	BOXHCC00055065	50
HCC00060070	60	70	12	2	0,33	BOXHCC00060070	50
HCC00063073	63	73	12	2	0,35	BOXHCC00063073	50
HCC00065075	65	75	12	2	0,38	BOXHCC00065075	50
HCC00065080	65	80	12	2	0,40	BOXHCC00065080	50
HCC00070080	70	80	12	2	0,43	BOXHCC00070080	50
HCC00070085	70	85	12	2	0,45	BOXHCC00070085	25
HCC00075090	75	90	12	2	0,53	BOXHCC00075090	25
HCC00080090	80	90	12	2	0,55	BOXHCC00080090	25
HCC00080095	80	95	12	2	0,58	BOXHCC00080095	25
HCC00085100	85	100	15	2	0,77	BOXHCC00085100	25
HCC00090105	90	105	15	2	0,86	BOXHCC00090105	25
HCC00100115	100	115	15	2	1,05	BOXHCC00100115	25
HCC00110125	110	125	15	2	1,34		
HCC00110130	110	130	15	2	1,40		
HCC00120140	120	140	18	2	2,00		
HCC00125145	125	145	18	2	2,11		
HCC00140160	140	160	18	2	2,67		
HCC00150170	150	170	20	2	3,33		
HCC00160180	160	180	20	2	3,79		

MATERIALE - MATERIAL:
ACCIAIO - STEEL - STAHL S355J0 (Fe510C) - S355JR (A105)

THESE PLUGS CAN BEND UNDER PEAK PRESSURE. WE RECOMMEND TO WELD ENDS TO ACHIEVE EXTRA RIGIDITY OTHERWISE USE INTERNAL END-PLUGS "HCCFI" TYPE.

IN CASE OF CONTINUOUS WORK PLEASE USE "HCMP" END-PLUGS.